





CASSPIR Mine Protected Armoured Personnel Carrier

- Factory re-manufactured
- The bench mark in mine protection
- Born in Africa for Africa
- Personnel carrier, ambulance, command vehicle
- Guaranteed supply of spares













BASIC SPECIFICATIONS CASSPIR MK2 MINE PROTECTED APC



ENGINE

Type ADE352 Non-turbo and Turbo direct injection

Configuration 6 Cylinders Displacement 5675 cc

Max. Power 124 kW (165 hp) @ 2800 r/pm.

Max. Torque 520 Nm @ 1600 r/pm.

Fuel Type Diesel

TRANSMISSION

Type Synchromesh DB G 3/60-5/7,5

No. of gears 5 Speed

TRANSFER CASE

Type Mercedes Benz VG500 2-speed with selectable 4 x 4

STEERING

Type Power assisted

Right hand drive orientation Left hand drive conversion available

BRAKES

Service brakes Air over hydraulic

Park brake Pneumatically contracting spring

Auxiliary brake Engine exhaust brake

SUSPENSION

Springs Semi elliptic leaf springs

Shock absorbers Double acting telescopic hydraulic

WHEELS AND TYRES

Rims Solid rim 10.00 x 20

Tyre size 14.00 x 20 - 18 Ply Multi Purpose

CONFIGURATION

Seating: Total crew Driver + Co-driver + 12 (14)

Models Armoured Personnel carrier, Ambulance, Command

Entrance doors Double doors at the rear

FITMENTS

Air conditioner Optional Extra
Seat belts Fitted to all seats

ELECTRICAL SYSTEM 12 Volt

DIMENSIONS

Overall length 6900 mm
Overall width 2450 mm
Overall height 3125 mm
Ground clearance (min.) 350 mm

Turning radius 8,5m kerb-kerb

Fuel capacity 220 litre

VEHICLE MASS

Tare 9480 kg
Gross vehicle mas (GVM) 10880 kg
Payload 1400 kg

PERFORMANCE

Max. speed 90 km/h Sustained road speed 80 km/h

Fuel autonomy 800 km on paved roads

Max. gradient 55%

PROTECTION

Ballistic B6 (7,62 x 51mm NATO Ball.)

Mine: 3 x TM57 blast mine (21kg TNT) under any wheel and 2 x TM57

(14kg) under the hull.



Specifications are subject to change without prior notice

P.O.Box 11296, Hatfield, 0028, Republic of South Africa Tel: +27 (12) 802 1200/1/2/3, Fax: +27 (12) 802 1204 E-mail: offroad@ott.co.za Website: www.ott.co.za