



- OPTIONAL REARWARD FACING SEATS
- NATO LITTER CAPABLE
- OPTIONAL JERRY CAN & SPARE TIRE HOLDERS
- ANTI RATTLE MOUNTING BRACKETS

MODULAR CARGO BED

TOOL-LESS COLLAPSING ROLL-CAGE (CV-22 TRANSPORTABLE)

KEYLESS IGNITION

ELECTRONIC POWER STEERING (EPS)

4 POINT HARNESS SEAT BELTS

OPTIONAL IR LIGHTING

ON-DEMAND TRUE ALL-WHEEL DRIVE (AWD)

COMMON SIZE BEADLOCK TIRES

88 HP PROSTAR™ ENGINE

Shown with additional upfits and accessories.

MRZR 2™ & MRZR 4™

TRANSPORTABLE, AGILE, MOBILITY.



SUSTAINMENT:

- Spares: SOFSA, DLA, GSA, NAMSA, DIRECT
- Technical Support Around the Globe
- Mechanic and Operator Training

FIELDIED BY:

- U.S. and Allied Special Forces
- Law Enforcement Agencies
- Emergency Response Teams

PROCUREMENT:



GS-07F-0398M



090512-PSI

DLA CONTRACT: LTCSPM8EC-13-D-0016

POLARISDEFENSE.COM

1-866-468-7783

INFO@POLARISDEFENSE.COM

SPECIFICATIONS

POLARISDEFENSE.COM

1-866-468-7783

INFO@POLARISDEFENSE.COM

MRZR 2™

MRZR 4™

	MRZR 2™	MRZR 4™
ENGINE	ENGINE TYPE	POLARIS PROSTAR™ 900 4-STROKE DOHC TWIN CYLINDER
	DISPLACEMENT	875CC
	FUEL SYSTEM	ELECTRONIC FUEL INJECTION
	HORSEPOWER	88 HP
	TOP SPEED	60 MPH / 96 KM/H
DRIVE TRAIN	TRANSMISSION/FINAL DRIVE	CONTINUOUS VARIABLE TRANSMISSION (CVT): P/R/N/L/H
	DRIVE SYSTEM	ON-DEMAND TRUE ALL-WHEEL DRIVE (AWD)
	ENGINE BRAKING SYSTEM / ACTIVE DESCENT CONTROL	STANDARD/STANDARD
SUSPENSION	FRONT SUSPENSION	DUAL A-ARM WITH 12.5 IN. / 31.75 CM TRAVEL
	REAR SUSPENSION	TRAILING ARM WITH 12.5 IN. / 31.75 CM TRAVEL
	SHOCKS	FOX PODIUM X 2.5 (COMP ADJUST/RES.)
BRAKES	FRONT/REAR BRAKES	4-WHEEL HYDRAULIC DISC WITH DUAL-BORE FRONT AND SINGLE-BORE REAR CALIPERS
	PARKING BRAKE	PARK IN TRANSMISSION
TIRES/WHEELS	FRONT TIRES	MOAPA AT/26 X 9-14 DWT
	REAR TIRES	MOAPA AT/26 X 9-14 DWT
	WHEELS	BEAD LOCK
DIMENSIONS/CAPACITIES	WHEELBASE	81.4 IN. / 206.8 CM
	DRY WEIGHT	1611 LB. / 730.7 KG
	OVERALL VEHICLE SIZE (L X W X H)	115.4 X 60 X 73.6 IN. / 293.1 X 152.4 X 187 CM
	HEIGHT W/ COLLAPSED ROLL CAGE	60 IN. / 152.4 CM
	GROUND CLEARANCE	11.2 IN. / 28.4 CM
	FUEL CAPACITY	7.25 GAL / 27.4 L
	BED BOX DIMENSIONS (L X W X H)	33.75 X 45.75 X 20.5 IN. / 85.73 X 116.2 X 52.1 CM
	FRONT/REAR RACK OR BOX CAPACITY	500 LB. / 226.8 KG
	PAYLOAD CAPACITY	1,000 LB. / 453.6 KG
	PASSENGERS	2 (4 WITH OPTIONAL REARWARD FACING SEATS)
	LITTER CAPACITY	1
	HITCH TOWING RATING	1500 LB. / 680.4 KG
	HITCH/TYPE	STANDARD/2" RECEIVER
	FEATURES	SEATING
SEATBELTS		FOUR-POINT HARNESSSES WITH QUICK RELEASE LATCH
KEYLESS IGNITION		STANDARD
TILT STEER WHEEL / PASSENGER GRAB BAR		STANDARD
AIRCRAFT TIE-DOWNS		FRONT AND REAR OF VEHICLE
CARGO SYSTEM		POLARIS METAL RACKS WITH QUICK RAIL SYSTEM
WINCH		POLARIS 3,500 LB. WINCH
LIGHTING		WHITE LED(HIGH/LOW), BLACK-OUT DRIVE AND OEM IR LIGHT WIRE HARNESS
ELECTRONIC POWER STEERING		STANDARD
COLOR		MILITARY TAN
INSTRUMENTATION		DIGITAL GAUGE, SPEEDOMETER, ODOMETER, TACHOMETER, TRIPMETER, HOUR METER, CLOCK, GEAR INDICATOR, FUEL GAUGE, HI-TEMP/LOW-BATT LIGHTS, DC OUTLETS (2)

MRZR 2™

MRZR 4™




INTERNAL AIR TRANSPORT CERTIFIED:

V22, H-53, H-47



VEHICLE MODULARITY:



POLARIS
DEFENSE

All pricing, specifications, claims and information contained in this brochure are based on information available at the time of publication. Polaris assumes no responsibility for any inaccuracies, opinion, or omissions in those publications. All pricing, specifications, and descriptions are subject to change without notice, and Polaris assumes no responsibility for changes in pricing or specifications. ©2014 Polaris Industries Inc.